

NAR-5000 Specification List:



Simultaneously recording channels	8,16, 24,32
Recording interface	RJ-11
Available hard disk capacity	500GB, 1TB&2TB are selectable
Displayer	Touch Screen 5" TFT
Maximum Recording Time	>140,000H
Start recording mode	timing, reversed polarity, keying, Voice Activated
Off hook detect voltage	<(3-80)V
On hook detect voltage	>(10-100)V
CID detected signal	DTMF/FSK
CID detect intensity range	0 dB to -32dB
Affected Frequency range	100 Hz to 3400 Hz
Input impedance	AC: 100K, DC: 5.1M
Signal-to-crosstalk ratio	> 60 dB
S/N ratio	> 70 dB
Input voltage	DC19V
Input voltage range	DC18V-DC24V
Operating current	1.5A
Maximum current	3A
Rating power consumption	10W
Battery type	2*12V/2C lead-acid batteries in series
Operating Temperature	0°C to 40°C
Operating Humidity	10% to 90 %
Network interface	RJ-45
Accessories	DC19v power adapter, software, User Manual, DB37*2 RS232
Dimension(L*W*H) CM	43*39*9cm
Packing dimension(L*W*H) CM	55*48*15cm
Net weight	6.6kg
Gross weight	9.1kg