


## NAR4004/NAR4008(4ch/8ch) Standalone Telephone Recorder Specification

Picture	
Channel	4,8
Storage	HDD or SD card (Max.SD 64G or 2.5' HDD500GB )
LCD	5" TFT800 *480 Touch Screen
Recording Format	ADPCM
Compression Ratio	4KB/S
Recording Trigger Mode	Voltage/ Voice/ Hot key
Off hook detect voltage	3-80V
On hook detect voltage	10-100V
Support CID	DTMF/FSK
CID detect intensity range	0 dB to -32dB
Recording Frequency range	100 Hz to 3400 Hz
Input impedance	AC : 100K · DC : 5.1M
S/N ratio	> 60 dB
Signal-to-crosstalk ratio	> 70 dB
Input voltage	DC19V
Rating operating current	1.5A
Maximum current	3A
Rating power consumption	30W
Optional Battery	
Operating Temperature	0°C to 40°C
Operating Humidity	10% to 90 %
Network interface	RJ-45
Accessory	RJ11 cord · RS232 cable, power adaptor, CD
Dimension L*W*H	25.2cm*17.6cm*4.6cm
Package	
Net Weight	
Gross Weight	

**Notice: NAR-4004 and NAR-4008 is without the touch screen. If you need the screen, need add price USD65.00, realize the new model NAR-4004S and NAR-4008S.**